

SAFETY DATA SHEET

Issuing Date: 27-March-2023

Revision Date: 27-March 2023

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name: Valve Regulated Lead-Acid Battery

VABO Sealed Lead-Acid (non-spillable) battery. **Type:**

PM-series;

59004, 59014, 59201, 59202, 59207, 59211, 59216, 59217, 59220, 59224, 59221, 59209, 59222, 59225, 59256

UPS-series

59232,59233,59257

Other means of identification

Synonyms: None

Recommended use of the chemical and restrictions on use

Recommended Use:	Lead-Acid (Non-Spillable) Battery
Uses advised against:	No information available

Details of the supplier of the safety data sheet

Supplier Name:	VABO NV
Supplier Address::	Boterbosstraat 20, 3550 Heusden-Zolder, Belgium
Supplier Phone Number:	Phone:+32 13 350550
	Fax:+32 13 350558
	Contact Phone:+886-49-2254777

Supplier Email:info@vabo.beSupplier Website:www,vabo.beEmergency telephone number:+32 13 350550

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Gases)	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A

Reproductive toxicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Harmful if swallowed Harmful if inhaled Causes severe skin burns and eye damage Causes serious eye irritation May cause cancer May damage fertility or the unborn child **May cause damage to organs through prolonged or repeated exposure**



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance: Gray black cuboid battery Physical State: Solid Odor: Odorless

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.6% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

※PBB spices or PBDE spices is not involved

Chemical	CAS No	Weight-%	Trade Secret
Lead	7439-92-1	45 ~ 60%	*
Lead dioxide	1309-60-0	15 ~ 25%	*
Sulfuric acid (Electrolyte)	7664-93-9	15 ~ 20%	*
Calcium (Lead calcium alloy)	7440-70-2	<0.06%	*
Tin	7440-31-5	<0.6%	*
Arsenic (Inorganic)	7440-38-2	<0.0006%	*
Non-Hazardous Materials	N/A	5 ~ 10%	*

(The non-hazardous materials include ABS plastic, glass fiber, rubber, copper, expoxide-resin glue)

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice S Eye Contact First aid is upon rupture of sealed battery. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open

Issuing Date: 27-March-2023	Revision Date: 27-March 2023	
	while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and easy to do. Continue rinsing.	
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Inhalation	Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.	
Ingestion	Do NOT induce vomiting. Rinse mouth. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.	
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).	
Most important symptoms and effects, both acute and delayed		
Most Important Symptoms and Effects	Burning sensation. Lead poisoning is characterized by a metallic taste in the mouth, loss of appetite, indigestion, nausea, vomiting, constipation, sleep disturbances and overall weakness. Severe exposures can lead to shock, circulatory collapse and death.	
Indication of any immediate medical attention and special treatment needed		
Notos to Physician a	Treat symptometically. Product is a corrective material	

Notes to Physician sTreat symptomatically. Product is a corrosive material.
Use of gastric lavage or emesis is contraindicated.
Possible perforation of stomach or esophagus should be
investigated. Do not give chemical antidotes. Asphyxia
from glottal edema may occur. Marked decrease in blood
pressure may occur with moist rales, frothy sputum and
high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code	Corrosive: Acid-liquid Toxic: Liquid
Hazardous Combustion Products Carbon oxides	
<u>Explosion Data</u> Sensitivity to Mechanical Impact	No
Sensitivity to Static Discharge	No
Drotoctive equipment and pressutions fo	r firafiabtara

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Attention! Corrosive material. Avoid contact with skin, eyes or clothing.
Other Information	Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust.

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions for safe handling Handling I	In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.		
Conditions for safe storage, including any incompatibilities			
Storage Incompatible products	Keep containers tightly closed in a dry, cool and well- ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials. Acids. Bases. Oxidizing agent.		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lead 7439-92-	TWA: 0.05 mg/m3	TWA: 50 μg/m3 TWA: 50 μg/m3	IDLH: 100 mg/m3 TWA:
1		Pb	0.050 mg/m3
		Action Level: 30 µg/m3 Poison,	
		See 29 CFR 1910.1025 Action	
		Level: 30 µg/m3 Pb Poison, See	
		29 CFR 1910.1025	
Lead dioxide 1309-60-	TWA: 0.05 mg/m3 Pb	TWA: 50 µg/m3 Pb	IDLH: 100 mg/m3 Pb TWA:
0		Action Level: 30 µg/m3 Pb	0.050 mg/m3 Pb
		Poison, See 29 CFR 1910.1025	
Sulfuric acid 7664-93-	TWA: 0.2 mg/m3 thoracic	TWA: 1 mg/m3 (vacated)	IDLH: 15 mg/m3 TWA:
9	fraction	TWA: 1 mg/m3	1 mg/m3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and

Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

	Showers
Engineering Measures	Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection	None required for consumer use. If splashes are likely to occur: Face protection shield.
Skin and Body Protection	Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Physical and Chemical</u> <u>Properties</u> Physical State Appearance Color	Solid Cuboid battery Gray black	OdorOdorlessOdorNo informationThresholdavailable
Property pH Melting / freezing point Boiling point / boiling range Flash Point Evaporation Rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit Lower flammability limit	Values No data available 327.4°C 1740°C No data available No data available No data available No data available No data available	Remarks Method None known Lead Lead None known None known None known
Vapor pressure Vapor density Specific Gravity Water Solubility	<0.3mmHg @25°C 3.4 1.170-1.40 100% No data available No data available No data available No data available No data available No data available	Electrolyte Electrolyte Electrolyte None known None known None known None known None known None known

Page: 7/15

Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing Properties

Other Information Softening Point VOC Content (%) Particle Size Particle Size Distribution No data available No data available

No data available No data available No data available

Revision Date: 27-March 2023

Valve Regulated Lead-Acid Battery

10. STABILITY AND REACTIVITY

Reactivity No data available.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous

<u>Reactions</u> None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Exposure to air or moisture over prolonged periods. Avoid shorting circuit or sparks near battery. Avoid prolonged over-charging. Use only approved charging methods. Do not charge in gas tight containers. Keep battery away from strong oxidizers, sparks, open flames.

Incompatible Materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based
	on known or supplied information.
Inhalation	Specific test data for the substance or mixture is not
	available. Corrosive by inhalation. (based on
	components). Inhalation of corrosive fumes/gases may
	cause coughing, choking, headache, dizziness and
	weakness for several hours. Pulmonary edema may

Information on likely routes of exposure

information on likely routes	
	occur with tightness in the chest, shortness of breath,
	bluish skin, decreased blood pressure and increased
	heart rate.
	Inhaled corrosive substances can lead to a toxic edema
	of the lungs.
	Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not
,	available. Causes burns (based on components).
	Corrosive to the eyes and may cause severe damage
	including blindness. Expected to be an irritant based on
	components.
Skin Contact	Specific test data for the substance or mixture is not
	available. Corrosive (based on components). Causes
	burns.
Ingestion	Specific test data for the substance or mixture is not
ingestion	
	available. Causes burns (based on components).
	Ingestion causes burns of the upper digestive and
	respiratory tracts. May cause severe burning pain in the
	mouth and stomach with vomiting and diarrhea of dark
	blood. Blood pressure may decrease. Brownish or
	yellowish stains may be seen around the mouth. Swelling
	of the throat may cause shortness of breath and choking.
	May cause lung damage if swallowed. May be fatal if
	swallowed and enters airways. Ingestion may cause
	irritation to mucous membranes. Ingestion may cause
	gastrointestinal irritation, nausea, vomiting and diarrhea.
	May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Sulfuric acid 7664-93-	= 2140 mg/kg (Rat)	-	= 510 mg/m3 (Rat) 2 h
9			

Information on toxicological effects Symptoms Erythe

Erythema (skin redness). Burning. May cause blindness. Coughing and/or wheezing. May cause redness and tearing of the eyes.

Delayed and immediate effects as well as chronic effects from short and long-termexposureSensitizationNo information available

Mutogenic Effects Carcinogenicity No information available No information available The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lead 7439-92- 1	A3	Group 2A	Reasonably Anticipated	Х
Lead dioxide 1309-60- 0	A3	Group 2A	Reasonably Anticipated	Х
Sulfuric acid 7664-93- 9	A3	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans NTP (National Toxicology Program) Known - Known Carcinogen Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X – Present				
Reproductive Toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard. Contains a known or			
Developmental Toxicity	suspected reproductive toxin. Contains ingredients that have suspected developmental hazards.			
STOT - single exposure STOT - repeated exposure	No information available Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).			
Chronic Toxicity	Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming			
Target Organ Effects Aspiration Hazard	system and the reproductive system. Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Reproductive System. Blood. Central Nervous System (CNS). Gingival Tissue. Kidney. Teeth. Cardiovascular system. Hematopoietic system. Immune system. May damage the unborn child. No information available.			
-				

<u>Numerical measures of toxicity Product Information</u> The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 500.00 mg/kg ATEmix (inhalation-gas) 5,625.00 ppm (4 hr) ATEmix (inhalation-dust/mist) 1.10 mg/l ATEmix (inhalation-vapor)

14.00 ATEmix

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead 7439-92- 1		96h LC50: = 0.44 mg/L (Cyprinus carpio) 96h LC50:= 1.17 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.32 mg/L (Oncorhynchus mykiss)		48h EC50: = 600 μg/L
Sulfuric acid 7664-93- 9		96h LC50: > 500 mg/L (Brachydanio rerio)		24h EC50: = 29 mg/L

Persistence and

Degradability No

information available.

Bioaccumulation

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging	Dispose of contents/containers in accordance with local regulations.
US EPA Waste Number	D002 D004 D008

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Lead 7439-92-	(hazardous constituent -	Included in waste	= 5.0 mg/L regulatory	
1	no waste number)	streams:	level	
		F035, F037, F038, F039,		
		K002, K003, K005, K046,		
		K048, K049, K051, K052,		
		K061, K062, K064, K065,		
		K066, K069, K086, K100,		
		K176		

California Hazardous Waste Codes 792

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Lead 7439-92- 1	Тохіс
Lead dioxide 1309-60- 0	Тохіс
Sulfuric acid 7664-93- 9	Toxic Corrosive

14. TRANSPORT INFORMATION

Transportation Information

Since VABO batteries meet the requirement of "Non-Spillable" and Exempt from Hazardous Goods regulations, they can be transported by Air, Sea, or Land transportation. All batteries are labeled as "Non-Spillable" individually. Therefore, VABO batteries are not suitable for NA or UN number.

U.S. DOT :

DOT-Our Non-spillable batteries are **Not subject to DG regulations**, since they meet the requirements of 49 CFR 173.159(d). They do not have an assigned UN number nor do they require additional DOT hazard labeling.

EU- ADR/RID: New and spent batteries are exempt from all ADR/RID (Special Provision 598)

IATA / ICAO :

IATA/ICAO- **VABO** batteries are exempt from **DG regulations**, and classified as a "Non-Spillable battery". Our Non-spillable batteries are **Not subject to DG regulations**, since they meet the requirements of Packing Instructions **872** of Special Provision A67. The **VABO** batteries are securely packaged, protected from short circuits and labeled "Non-Spillable". They are good for transportation on either passenger aircraft or cargo aircraft.

<u>For all modes of transportation, each battery and outer package must be labeled</u> : "Non-Spillable" or "Non-Spillable Battery". This label must be visible during transportation.

IMDG:

VABO batteries are Non-spillable batteries. They meet the requirements of Special Provision 238 and are not subject to the provisions of the IMDG code.

15. REGULATORY INFORMATION

TSCA DSL Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Lead - 7439-92-1	7439-92-1	45 - 60	0.1
Lead dioxide - 1309-60-0	1309-60-0	15 – 25	0.1
Sulfuric acid - 7664-93-9	7664-93-9	15 - 20	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants		CWA - Hazardous Substances
Lead - 7439-92-1		x	x	
Lead dioxide - 1309-60-0		x		
Sulfuric acid - 7664-93-9	1000 lb			x

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Lead 7439-92- 1	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ
Sulfuric acid 7664-93- 9	1000 lb	1000 lb	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
	Carcinogen
Lead - 7439-92-1	Developmental
	Female Reproductive
Lead dioxide - 1309-60-0	Carcinogen
	Developmental
	Female Reproductive
	Male Reproductive
Sulfuric acid - 7664-93-9	Carcinogen

Arsenic - 7440-38-2

Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lead 7439-92- 1	X	X	х	X	х
Lead dioxide 1309-60- 0	X	X	X	X	Х
Sulfuric acid 7664-93- 9	X	X	Х	X	Х
Tin 7440-31- 5	X	X	Х		
Calcium 7440-70- 2	X	X	X		

International Regulations

Mexico National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Lead	A3	Mexico: TWA= 0.15 mg/m3
7439-92-1 (45 - 60)		
Lead dioxide 1309-60-0	A3	Mexico: TWA 0.15 mg/m3
(15-25)		_
Sulfuric acid 7664-93-9	A2	Mexico: TWA 1 mg/m3
(15-20)		

Mexico - Occupational Exposure Limits - Carcinogens

A2 - Suspected Human Carcinogen


A3 - Confirmed Animal Carcinogen

Canada WHMIS Hazard Class

Non-controlled

EU Regulation:

In accordance with EU2006/66/EC Battery Directive, VRLA batteries should present crossed-out wheeled bin symbol of lead together with the ISO recycling symbol. Does not contain any mercury,Hg, (<0.0005%) or cadmium, Cd, (<0.002%).



	16. UTHER INFORMATION	N
NFPA HMIS	Health Hazards Flammability Instability Physical and Chemical Hazards Health Hazards Flammability Physical Hazards Personal Protection	3 0 0 x 0 0 0 X
Prepared By Issuing Date Revision Date Revision Note	VABO NV 27-Mar-2023 27-Mar-2023 No information available	

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release; and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet